

# Low Cost **kleuren** printer



Description	3400
Print method	Serial inkjet dot matrix (Max. 720 dpi × 360 dpi)
Print fonts	Not equipped with print fonts; prints all data as the graphic data
Barcodes	This printer does not have a barcode / two-dimensional symbol encoding function. Following barcode / two-dimensional symbol data (graphic data) are provided by EPSON Windows driver. Barcodes: UPC-A, UPC-E, JAN13(EAN), JAN8(EAN), Code39, ITF, Codabar, Code93, Code128, GS1-128, GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded 2-dimensional symbols: PDF417, QR Code, Maxi Code, GS1 DataBar Stacked, GS1 DataBar Stacked Omnidirectional, GS1 DataBar Expanded Stacked, Composite Symbology, DataMatrix, Aztec
Interfaces	USB 2.0 or Ethernet IEEE 802.3
Print speed	Max. 92 mm / sec. (printing width: 56 mm, 360 dpi × 180 dpi, bi-directional printing)
Paper	Plain paper, Fine paper, Die-cut label Width: 25.4 to 108 mm (label width) Thickness: Plain paper: 0.128 mm, Fine paper: 0.145 mm
Printing width	Max. 104 mm
Ink cartridge	SJIC15P (3-color combined, pigment ink)
Autocutter	Full cut auto cutter included
Overall dimensions (mm)	255 (W) × 275 (D) × 261 (H)
Safety Standards	UL / CSA / TÜV (EN60950-1)
Operating System	Microsoft Windows 2000 SP4, Microsoft Windows XP SP3, Microsoft Windows SP2, Microsoft Windows Vista SP1 (Only 32 bit Version support)

**JALO** coding & labeling bv



Van Oldenbarneveldtstraat 114  
6827 AN Arnhem  
Postbus 173, 6800 AD Arnhem  
Tel. 0031 (0) 26 - 3634274  
Fax. 0031 (0) 26 - 3634319  
sales@jalo.nl - www.jalo.nl